



OCULAR IQ COMMERCIAL SERIES

IOCAW05C-7S / IOCAW05C-22S

Ocular IQ Commercial provides a high quality and cost-effective EV charging point designed to offer full Mode 3 fast charging to any EV in Australia.

With OCPP1.6J integration, the charger can be connected to any charging management system for easy operation, monitoring, and maintenance.

MAIN FEATURES

- 7" LED Display with instant feedback
- Robust commercial-grade metallic housing
- IEC 61851-1 Mode 3 fast charging
- Universal Type-2 socket
- Charging speeds - 7kW (32A) or 22kW (32A)
- Built-in overload and fault current protection
- Built-in LED charging status indicator
- Built-in RCCB Type-B
- IP grade 54 IEC 60529
- Full OCPP 1.6J

01

OCPP profiles 1:

Firmware Management and Remote Trigger

02

OCPP profiles 2:

Smart Charging

03

OCPP profiles 3:


Local Auth List Management and Reservation



SPECIFICATION DATASHEET

	Model	IOCAW05C-7S	IOCAW05C-22S
Power Input	Input Rating	1-Phase 230V +/-20%, 32A	3-Phase 400V +/-20%, 32A
	Standby Power	< 5W	
Power Output	Output Rating	7kW 1-Phase, 32A	22kW 3-Phase, 32A
	Internal Residual Current Detection	CE Certified RCCB Type-B	
Protection	Over Current Protection	NA	
	Lightning Protection	NA	
	Energy Meter	MID Certified	
	Electrical Protection	Over current, short circuit, over voltage, under voltage, ground fault, lightning surge, over temperature	
User Interface & Control	Status Indicators	LED light indicating state of charger: charging, faulty, or available	
	Display	7" LCD Display	
	User Authentication	RFID card reader. ISO/IEC 156963 and 14443	
	Buttons/Switches	Physical button for charging connector selection and output current adjustment	
Environmental	Operating Temperature	(-30 C to +50 C) in operation, (-40 C to +70 C) in storage	
	Humidity	5% - 95% without condensation	
	IP Degree of Protection	IP54 off load conforming to IEC 61851-1 IP54 on load conforming to IEC 61851-1	
	IK Degree of Protection	IK10 charging station conforming to IEC 61851-22 IK10 socket-outlet conforming to IEC 61851-22	
Mechanical	Mounting Type	Mounted or Pedestal Options	
	Dimension (W x H x D)	270 x 400 x 130 mm	
	Net Weight	10kg (socket) / 12.4kg (cable)	11.2kg (socket) / 13.8 (cable)
Communication	Network Interface	Ethernet, (2.4G/5G Wi-Fi)	
	OCPP	OCPP 1.6J	
Regulation	Certificate	IEC/ EN 61851-1, IEC/EN 61851-21-2, IEC/ EN 61000-3	
	Charging Interface	IEC 62196 Type 2 socket with cable lock	

OCULAR



Size	A	B	C
270 x 400 x 130 mm	270	400	130



ocularcharging.com.au
sales@ocularcharging.com.au
1300 912 650